



The weighing rings are designed to control the quantity of material entering the material receiver, that is discharged into the hopper and then into the press.

The weighing rings interface with the material receivers and are managed directly by the control panel of the centralized feeding system.



MATRIX							10 / 10 / 2014 10 : 53 : 05	
	Receiver	Material	Prod. Target Kg/h	Start time	Totalizer Kg	Totalizer Kg/h	Efficiency %	
<input type="checkbox"/>	1 IMM 1	ABS	50.0	08 / 10 / 2014 14 : 09	47214	47.1	94.2	
<input type="checkbox"/>	2 IMM 2	PP	0.0	00 / 00 / 0000 00 : 00	0	0.0	0	
<input type="checkbox"/>	3 IMM 3	PA	0.0	00 / 00 / 0000 00 : 00	0	0.0	0	
<input type="checkbox"/>	4 IMM 4	PEEK	0.0	00 / 00 / 0000 00 : 00	0	0.0	0	
<input type="checkbox"/>	4 IMM 5	PET	0.0	00 / 00 / 0000 00 : 00	0	0.0	0	
<input type="checkbox"/>	5 IMM 6	POM	0.0	00 / 00 / 0000 00 : 00	0	0.0	0	
<input type="button" value="Reset"/> <input type="button" value="Stop"/>								

	Unità di misura	MWS210	MWS210
Hole diameter	∅	210	280
Outer diameter	∅	233	303
Internal diameter	∅	156	216
Height	mm	65	65

Material consumption						10 / 10 / 2014 10 : 53 : 56	
	Material	Start time	Stop time	Kg	Totalizer Kg/h		
<input type="checkbox"/>	ABS	10 / 10 / 2014 10 : 49	00 / 00 / 0000 00 : 00	17214	43.1		
<input type="checkbox"/>	PP	09 / 10 / 2014 09 : 20	00 / 00 / 0000 00 : 00	0	0.0		
<input type="checkbox"/>	PA	00 / 00 / 0000 00 : 00	00 / 00 / 0000 00 : 00	0	0.0		
<input type="button" value="Reset"/> <input type="button" value="Stop"/>							

<<< Pagina lasciata intenzionalmente bianca >>>